

# APPENDIX I - SPECIFICATIONS

<b>JET 3 ULTRA SPECIFICATIONS</b>	
Suspension:	Active-Trac
Drive Wheels:	10 in. (25.4 cm) pneumatic or solid available
Caster Wheels:	8 in. (20.32 cm) solid, rear-mounted
Anti-tip Wheels:	6 in. (15.24 cm) solid, front-mounted
Maximum Speed: <sup>1</sup>	Up to 4 mph (6.44 km/h)
Range: <sup>1,3</sup>	Up to 11 miles (17.7 km)
Brakes:	“Intelligent Braking” electronic regenerative, disc park brake
Ground Clearance: <sup>2</sup>	See figure 29.
Turning Radius: <sup>2</sup>	See figure 29.
Overall Size: <sup>2</sup>	Length: See figure 29. Width: See figure 29.
Drivetrain:	Two motor, mid-wheel drive
Batteries: <sup>4,5</sup>	Two 12-volt, deep-cycle, U-1
Battery Charger:	3-amp, off-board
Weight Capacity:	300 lbs. (136 kg)
Component Weights: <sup>2</sup>	Base: 92 lbs. (41.74 kg) Medium-back Seat: 37 lbs. (16.78 kg) Batteries: 24.5 lbs. (11.11 kg) each

- <sup>1</sup> Varies with base model, user weight, terrain type, battery amp-hour rating (Ah), battery charge, battery condition, motors, controller type, tire type, and tire condition. This specification can be subject to variance of (+ or -) 10%.
- <sup>2</sup> Due to manufacturing tolerances and continued product improvement, this specification can be subject to variance of (+ or -) 3%.
- <sup>3</sup> Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- <sup>4</sup> AGM or Gel-Cell type required. See VI. “Batteries and Charging.”
- <sup>5</sup> Battery weight may vary based on battery manufacturer.

***NOTE: This product conforms to all applicable ANSI/RESNA testing requirements and ISO 7176 series EN12184 standards. All specifications subject to change without notice.***